International Journal of Trend in Scientific Research and Development (IJTSRD) Volume 3 Issue 5, August 2019 Available Online: www.ijtsrd.com e-ISSN: 2456 – 6470

Static Structural Analysis of Vented and Non Vented Disc Brake

Meesala Vanajakshi¹, Pothuraju. V. V. Satyanarayana², E. Lakshmi Devi³

¹Post Graduate Student, ^{2,3}Assistant Professor

^{1,3}Department of Mechanical Engineering, Visakha Technical Campus, Narava, Visakhapatnam, India ²Department of Mechanical Engineering, Avanthi Institute of Engineering and Technology, ²Malauranalam, Visakhapatnam, India

²Makavarapalem, Visakhapatnam, India

How to cite this paper: Meesala Vanajakshi | Pothuraju. V. V. Satyanarayana | E. Lakshmi Devi "Static Structural Analysis of Vented and Non Vented Disc Brake" Published in

International Journal of Trend in Scientific Research and Development (ijtsrd), ISSN: 2456-6470, Volume-3 | Issue-5, August 2019, pp.721-727,



https://doi.org/10.5281/zenodo.7928783

Copyright © 2019 by author(s) and International Journal of Trend in Scientific Research and Development Journal. This is an Open Access article distributed

under the terms of the Creative Commons Attribution



License (CC BY 4.0) (http://creativecommons.org/licenses/by /4.0)

For example, in friction braking it is converted into heat, and in regenerative braking it is converted into electricity or compressed air etc. During a braking operation not all the kinetic energy is converted into the desired form, e.g. in friction braking some energy might be dissipated in the form of vibrations.

So to get optimum performance in demanding applications, ventilation is introduced in the brake discs which increases the cooling rate. Brake discs could be divided into two categories:

- 1. Ventilated disk brake
- 2. Non-Ventilated or Solid disk brake

2. PRINCIPLE OF BRAKING SYSTEM

A brake is a device by means of which artificial frictional resistance is applied to moving machine member, in order to stop the motion of a machine. Break play a major role in moving automotive vehicles.

A disk brake consists of a cast iron disc bolted to the wheel hub and a stationary hosing called caliper the caliper is connected to some stationary part of the vehicle like the axle casing or stub axle as in two parts each part containing a piston. in between each piston and the disc, there is a friction pad held in position by retaining pins, spring plates etc. passages are drilled in the caliper for the fluid enter or leave

ABSTRACT

The current study essentially deals with the modeling and analyzing vented and non vented disc brake by CATIA and ANSYS. Finite element models of the brake-disc are shaped with CATIA and simulated using ANSYS which is based on the finite element method. This study Structural analysis is done so as to get the strength of the disc brake. Here we discuss disc brake which is used in many vehicles. The stresses and variations developed in vented and nonvented disc brakes are discussed using ANSYS software. Disc gets stressed when used in slowing down or stopping the vehicle. So that by using Ansys we can observe variations between stresses of vented and non-vented disc brake. Disc brakes are mostly used on front wheels in two-wheelers, hatchback cars and also widely used on both front and rear wheels of high end cars.

The main aim of this paper is to minimize the Total deformation, Directional deformation, Equivalent stress and strain with best suited Material Analysis is done on both Vented and non vented disc brake. The Geometry of the models is carried out in the CATIA V5 R20 Software and is designed in Mechanical Design. The analysis part is done by using ANSYS R14.5 Software.

KEYWORDS: vented, Non vented, hatchback, Catia and Ansys

1. **CINTRODUCTION**entific

A vehicle requires a brake system to stop or adjust its speed with changing road and traffic conditions. The basic principle used in braking systems is to convert the kinetic energy of a vehicle into some other form of energy.

each housing the passages are also connected to another one for bleeding. Each cylinder and piston.

When the brakes are applied, hydraulically actuated pistons move the friction pads into contact with the rotating disc, applying equal and opposite forces on the disc. Due to the friction between disc and pad surfaces the kinetic energy of the rotating wheel is converted into heat, by which vehicle is to stop after a certain distance. On releasing the brakes the brakes rubber-sealing ring acts as return spring and retract the pistons and the friction pads away from the disc.

3. DESIGN OF DISC BRAKE

Designing of vented and non vented disc brake rotor using the ISO standard dimensions of BMW car in CATIA V5.



Fig 1: Three Dimensional Vented Disc brake



Fig 2: Three Dimensional Non Vented Disc brake

4. DESIGN CALCULATION BENDING TEST

The bending moment to be imparted in the test shall be in accordance with the following formula: $M = ((\mu^*R) + d)^* F^* S$

- M = Bending moment in 'Nm'
- μ = Friction Coefficient between the tire and the road surface(no units)
- R = Radius of the tyre applicable to the wheel in 'm' d = Offset of the wheel in 'm'
- F = Maximum load acting on the tire in 'N' S = Coefficient specified according to the standards.

Tyre specification Radial 315/60-R18

315 is the section width in millimeters 60 is the Aspect ratio in percentage

5. MATERIAL SELECTION

nternational Journal

It plays an important role in product design and manufacturing. This is guided by the way the material behaves in the real-time conditions according to its use. The material response to the environmental stimulus is called property. Based on the application and usage of material, its properties become significant.

Properties	Gray Cast Iron	Titanium Alloy	Stainless Steel
Density	7.2e-006 kg mm^-3	4.62e-006 kg mm^-3	7.75e-006 kg mm^-3
Young's Modulus	1.1e+005 MPa	96000 MPa 🥭	1.93e+005 MPa
Poisson's Ratio	0.28	0.36	0.31
Coefficient of Thermal Expansion	1.1e-005 C^-1	9.4e-006 C^-1	1.7e-005 C^-1
Specific Heat	4.47e+005 mJ kg^-1 C^-1	5.22e+005 mJ kg^-1 C^-1	4.8e+005 mJ kg^-1 C^-1
Thermal Conductivity	5.2e-002 W mm^-1 C^-1	2.19e-002 W mm^-1 C^-1	1.51e-002 W mm^-1 C^-1
Resistivity	9.6e-005 ohm mm	1.7e-003 ohm mm	7.7e-004 ohm mm

STATIC STRUCTURAL ANALYSIS

Workbench allows you to copy systems in order to efficiently perform and compare multiple similar analyses.

Static analysis is performed over a structure when the loads and boundary conditions remain stationary and do not change over Time. it is assumed that the load or field conditions are applied gradually.

6. RESULTS

TESTING AND VALIDATION OF VENTED & NON VENTED DISC BRAKE CROSS SECTION

MODEL	TOTAL DEFORMATION (mm)	EQUIVALENT STRESS (Mpa)	EQUIVALENT STRAIN
VENTED	0.0045958	8.9412	8.2068e-5
NON VENTED	0.051897	17.901	0.0001646
VENTED	0.0054448	8.7275	9.1893e-5
NON VENTED	0.055934	17.32	0.00018267
VENTED	0.002654	8.8766	4.6457e-5
NON VENTED	0.028952	17.707	9.2832e-5
	MODELVENTEDNON VENTEDVENTEDVENTEDVENTEDNON VENTED	TOTAL DEFORMATION (mm) VENTED 0.0045958 NON VENTED 0.051897 VENTED 0.0054448 NON VENTED 0.055934 VENTED 0.002654 NON VENTED 0.0028952	MODEL TOTAL DEFORMATION (mm) EQUIVALENT STRESS (Mpa) VENTED 0.0045958 8.9412 NON VENTED 0.051897 17.901 VENTED 0.00554448 8.7275 NON VENTED 0.055934 17.32 VENTED 0.002654 8.8766 NON VENTED 0.028952 17.707

 Tab 1: Comparison results for static structural Ansys

R is the construction type i.e., Radial 18 is the rim diameter in inches

According to the industrial standards:

$\mu = 0.7 \text{ R} = 0.333 \text{ m}$

d = 37 mm = 0.037m F=1400lbs = 1400 * 0.453 = 634.2 kg = 634.2 * 9.81 = 6221.5 N S = 1.5

Bending moment

 $M = ((\mu^* R) + d)^* F^* S$ = ((0.7 * 0.333) + 0.037) * 6221.5 * 1.5 = 2520.65 Nm

= 2520.05 Nm = 252065Nmm



Graph 1: Deformation of different disc brake models

6.1. STATIC ANALYSIS OF DISK BRAKE FOR VENTED 1. GRAY CAST IRON MODELS RESULTS AND ANALYSIS OF VENTED DISC Mass = 8.4311kg, Nodes = 34213, Elements = 18347. BRAKE



Fig 3: Geometry Diagram

Fig 5: Total deformation



Fig 6: Equivalent stress



Fig 7: Equivalent Elastic strain

2. TITANIUM ALLOY

Mass= 5.4099 kg, Nodes= 34213, Elements= 18347.





3. STAINLESS STEEL

Mass= 9.0751 kg, Nodes= 34213, Elements= 18347.



Fig 8: Total deformation



Fig 9: Equivalent stress

Fig 11: Total deformation



Fig 12: Equivalent stress



Fig 13: Equivalent Elastic strain

6.2. STATIC ANALYSIS OF DISC BRAKE FOR NON VENTED MODELS RESULTS AND ANALYSIS OF NON VENTED DISC BRAKE 1. GRAY CAST IRON Mass= 3.657kg, Nodes= 16537, Elements= 7967.



Fig 16: Total deformation



Fig 15: Mesh diagram

2. TITANIUM ALLOY

Mass= 2.3466kg, Nodes= 16537, Elements= 7967.

C: Stat Struct Ittanium alloy Total Deformation Type: Total Deformation Unit: mm Time: 1 29:04:2010 14:41 0.005934 Max 0.003504 0.007249 0.001249 0.0062149 0.0062149 0.0062149 0.0062149 0.0062149

Fig 19: Total deformation

3. STAINLESS STEEL

Mass= 3.9363kg, Nodes= 16537, Elements= 7967.



Fig 22: Total deformation





Fig 21: Equivalent Elastic strain

Fig 24: Equivalent Elastic strain

7. CONCLUSION

It is observed that the Vented type disc brakes can provide better Static Structural analysis than the Non Vented disc Brake. It provides useful design tools and improvement of the brake performance in the disk brake system. We can say that from all the values obtained from the analysis i.e. the Total Deformation, Equivalent Stress and Equivalent strain. exhibit that the vented disc is best-suited design. Comparing the different results obtained from the analysis, it is concluded that disk brake with vents and of material Stainless steel is observed best possible combination for the present application.

The finite element results show that the performance of disc brake used in this study of geometry and material properties.

8. REFERENCES

- [1] R. S. KHURMI and J.K.GUPTA, (2008). Machine Design, Division of S. Chand and Company Ltd, Ram Nagar New Delhi.
- [2] Joe Y. G. Cha, Analysis of disc brake instability due to friction-induced vibration, International of automotive technology, vol9, No 2, PP 169-171.
- [3] M. Bayat, The effect of ceramic in a combination of the functionally graded rotating disc, International journal of computational method, vol9, No 2,2012,22 pages.
- [4] Utz von Wagner, (2011) Influence of dynamic brake pad properties on automotive disc brake squeal, PAMM, vol11, Issue 1, Paper 345-346.

- [5] Haripal Singh and Harsh Deep Shergill, (2012) Thermal Analysis of Disc Brake Using Comsol International Journal on Emerging Technologies.
- [6] Daniel Das. A Christo Reegan Raj. V, Preethy. S and RamyaBharani. G. (2013). Structural and Thermal Analysis of
- [7] Disc Brake in Automobiles."International Journal of Latest Trends in Engineering and Technology.
- [8] V. Chengal Reddy, M. Gunasekhar Reddy and Dr. G. HarinathGowd (2013), Modeling and Analysis of FSAE Car Disc Brake Using FEM. International Journal of Emerging Technology and Advanced Engineering.
- [9] Guru Murthy Nathi1, T N Charyulu, K. Gowtham and P Satish Reddy,(2012), COUPLED STRUCTURAL THERMAL ANALYSIS OF DISC BRAKE, GURU MURTHY NATHI, et al ISSN: 2319 – 1163 Volume:1 Issue:4
- [10] K. NareshBabu and T.Siva Krishna, (2013) STRUCTURAL DESIGN AND THERMAL ANALYSIS OF CARDIAC BRAKE ROTOR. Babu, et al, International Journal of Advanced Engineering Research and Studies.
- [11] V. M. M. Thilak, R. Krishnaraj, Dr. M. Sakthivel, K. Kanthavel, Deepan Marudachalam and M. G, R.Palani, (2011)," Transient Thermal and Structural Analysis of the Rotor-Disc of Disc Brake", International Journal of Scientific & Engineering Research Volume 2, Issue 8.