# **Dynamic Analysis of Structural Steel Frame** Subjected to Transient Thermal Load

# Shiva Jayanth B S, M N Hegde

Department of Civil Engineering, Dr. Ambedkar Institute of Technology, Bengaluru, Karnataka, India

of Trend in Scientific

#### ABSTRACT

Fire is one of the most severe conditions to which structures can be subjected, and hence, the provision of appropriate fire safety measures for structural members is an important aspect of design. Recent years have seen significant research into the response of structural stainless-steel components, enabling the development and expansion of dedicated design guidance In this project work, dynamic analysis of structural steel frame subjected to transient thermal load is conducted. A two dimensional steel frame of length 3m and breadth 3m is modelled using ANSYS version R19.2. The Steel Frame is of single storey with fixed supports at the base. Transient Thermal load is applied at the joints of steel frame using ANSYS software. By using Finite Element Method, the performance of the steel frame is examined by dynamic analysis subjected to transient thermal load. The behaviour of steel frame under transient thermal load with respect to effect of temperature, rate of transfer of heat, frequency response and thermal analysis is studied.

KEYWORDS: Ansys, Steel Frame, Transient, Finite Element Analysis

### **INTRODUCTION**

can be subjected, and hence, the provision of appropriate fire safety measures for structural members is an important 245 potential losses due to structural failures caused by fire, and aspect of design. Recent years have seen significant research into the response of structural stainless-steel components. enabling the development and expansion of dedicated design guidance.

As a construction material, stainless steel offers great applicability due to its attractive appearance, strong corrosion resistance, easy maintenance and low life cycle cost. In addition, booming growth in the production of stainless steel along with its many varieties and continuing improvements in processing methods have paved the way for its increased use in building structures in recent years. Under the strong urge of the construction market, stainless steel as an architectural material is the new trend of civil engineering and is welcomed by many architects and structural engineers.

The design specifications for structures at normal service conditions are relatively mature, but because structure fires frequently occur, the security of the architectural structure is facing unprecedented challenge under fire conditions. Therefore, the behavior reaction and properties of structures in fire have gained attention in all countries, especially the new materials(such as stainless steel, aluminum alloy and glass)that are without any fire prevention measures for their aesthetic appearance, making the study of the mechanical properties of these structures particularly important.

Structural steel frames are widely used in virtually all types of buildings and industrial installations. Fire-resistant design *How to cite this paper*: Shiva Jayanth BS M N Hegde "Dynamic Analysis of Structural Steel Frame Subjected to

Transient Thermal Load" Published in International Journal of Trend in Scientific Research and Development (ijtsrd), ISSN: 2456-6470, Volume-4 |



Issue-6, October 2020, pp.109-114, URL: www.ijtsrd.com/papers/ijtsrd33264.pdf

Copyright © 2020 by author(s) and International Journal of Trend in Scientific **Research and Development Journal. This** is an Open Access article distributed

under the terms of the Creative **Commons Attribution** 



(CC 4.0) License BY (http://creativecommons.org/licenses/by (4.0)

Fire is one of the most severe conditions to which structures loo of structural steel framing is often required, depending on the fire risks associated with the structure, the magnitude of the accumulated performance record of similar structures in past fire incidents.

# METHODOLOGY IN ANSYS

In general, a finite element solution may be broken into the following four stages. This is a general guideline that can be used for setting up any finite element analysis.

- 1. Preferences
- 2. Preprocessing
- Solution 3.
- 4. General Post processing

### 1. Preferences

Select the Thermal option in electromagnetic modes to show in the GUI

Λ		Preferences for GUI Filtering	
[KEYW] Preferences	s for GUI Filtering		
Individual disciplin	e(s) to show in the GUI		
		Structural	
		I Thermal	
		ANSYS Fluid	
Electrom	agnetic:		
		Magnetic-Nodal	
		Magnetic-Edge	
		High Frequency	
		F Electric	
Note: If no individu	al disciplines are selected t	they will all show.	
Discipline options			
		h-Method	
	ОК	Cancel Help	

**Fig 1. Preferences Window** 

### 2. Pre-processing

Defining the problem; the major steps in preprocessing are given below:

- Define element type and material/geometric properties.
- Define key points/lines/areas/volumes.
- Modeling of the structure.
- Meshing of the structure.

### ANALYSIS RESULTS AND DISCUSSIONS A. MODEL SPECIFICATIONS:

A two dimensional steel frame of length 3m and breadth 3m is modelled as shown in figure below using ANSYS version R19.2. Steel Frame consists of single storey frame and the supports given are fixed supports at the ends. The input data for modelling and analysis are tabulated below.



Fig 5. Meshing of structure Window



Fig 8. CASE 1

**CASE 2**: Thermal load is applied at two joint upto 0.3m as shown in figure



Fig 9. CASE 2

**CASE 3**: Thermal load is applied at all joint upto 0.3m as shown in figure



Fig10. CASE 3

**CASE 4**: Thermal load is applied at one column as shown in figure



Fig 11. CASE 4

Applying different temperature loads as mentioned below for all the cases

- **Condition A** : Temperature of 250°C is applied at different time intervals of 600 seconds, 900 seconds and 1200 seconds.
- **Condition B** : Temperature of 500°C is applied at different time intervals of 600 seconds, 900 seconds and 1200 seconds.
- **Condition C** : Temperature of 1000°C is applied at different time intervals of 600 seconds, 900 seconds and 1200 seconds.

# C. ANALYSIS:

The considered steel frame with various conditions of thermal loading as per problem definition is analysed using ANSYS version R19.2. Effect of temperature and variation of temperature is compared.

# THERMAL ANALYSIS RESULTS

The defined problem is analysed for thermal loads and for the study of transfer of temperature, 3 nodes are selected at next to the load applied. The node numbers selected for the study of transfer of temperature are node number 25, node number 26 and node number 27.



Fig 12. - Node Numbers

The results are summarized with respect to different nodes and plotted graphs

### **RESULTS FOR THERMAL LOAD OF 250°C**

Thermal load of 250°C is applied for 600seconds, 900seconds and 1200seconds and the results extracted for Node numbers 25, 26 and 27 are as follows













1200 seconds

# 900 seconds



1200 seconds

# **RESULTS FOR THERMAL LOAD OF 500°C**

Thermal load of 500°C is applied for 600seconds, 900seconds and 1200seconds and the results extracted for Node numbers 25, 26 and 27 are as follows.



Graph 4: Temperature v/s Time curve for 500°C for 600 seconds

Thermal load of 1000°C is applied for 600seconds, 900seconds and 1200seconds and the results extracted for Node numbers 25, 26 and 27 are as follows.







Graph 8: Temperature v/s Time curve for 1000°C for 900 seconds



Graph 9: Temperature v/s Time curve for 1000°C for 1200 seconds

From above graphs, we can say that temperature is directly proportional to the time i.e, temperature increases with increasing time and temperature is indirectly proportional to the distance from the thermal load applied i.e, temperature decreases with increasing the distance from the thermal load.

From above graphs, temperature of Node 25 is greater when compared to Node 26 and Node 27 because Node 25 is nearer to the thermal load applied. Transfer of temperature decreases with increasing distance from the thermal load.

Thermal load of 250°C, 500°C and 1000°C is applied for 600 seconds and the results extracted for Node number 25, 26 and 27 are as follows







Graph 11: Temperature v/s Time curve for Node 26 for 600 seconds



Graph 12: Temperature v/s Time curve for Node 27 for 600 seconds

From above graphs, we can say that temperature is directly proportional to the thermal load applied ie, increase in thermal load increases the temperature in structure.

Temperature is directly proportional to the duration of thermal load applied ie, increase in duration of thermal load increases the temperature of the structure.

Thermal load of 250°C, 500°C and 1000°C is applied for 900 seconds and the results extracted for Node number 25, 26 and 27 are as follows

### **CONTOUR PLOTS FOR THERMAL LOAD OF 250°C**

Thermal load of 250°C is applied for 600, 900 and 1200 seconds and the contour results are as follows.



Fig 13. Contour plot for 250°C for 600seconds



Fig 14. Contour plot for 250°C for 900 seconds



Fig 15. Contour plot for 250°C for 1200 seconds

From above figure, we can say that there is a little rate of transfer of heat for 600sec, 900sec and 1200sec. Rate of transfer of heat decreases with the increase in distance. When thermal load is applied at one joint as shown in figure, there is no effect on other joints

### Conclusion

- Higher the intensity of thermal load applied, higher is the rate of transfer of heat along the length.
- The duration of thermal load on the surface is directly proportional to the rate of transfer of heat along the length. Therefore, longer the duration higher is the heat transferred.
- Rate of transfer of heat is not dependent on the portion of load applied *i.e.*, even if the load was applied at the

beam-column joint or the entire column, rate of transfer of heat to the adjacent members is same.

### References

- [1] M. Mehdi Mizazadeh, Martin Noel, Mark Green, (2017), Fatigue Behavior of Reinforced Concrete Beams with Temperature Differentials at Room, Journal of structural engineering, Volume 1.
- [2] M. Mehdi Mizazadeh, Mark F. Green, (2017), Non linear finite element analysis of reinforced concrete beams with temperature differentials Engineering Structures. Journal of Structural Engineering, ASCE, Volume 1.
- [3] Harshad D Mahale, (2016), Behaviour of steel structure under the effect of fire loading, Int. Journal of Engineering Research and Applications, Vol. 6, pp.42-46.
- [4] Li Guoqiang, Wang Peijun, Jiang Shouchao, (2015), Non-linear Finite Element Analysis of Axially Restrained Steel Beams at Elevated Temperatures in a Fire. Journal of Constructional steel research, Vol 63, pp. 1175-1183.
- Lenka lausova, Iveta Skotnicova, Vladimira Michalcova,
  (2015), Thermal Transient Analysis of Steel Hollow Sections Exposed to Fire. Perspectives in Science, Vol 7, pp. 247-252
- [6] IS-800 2007, General Construction in steel-Code of practice, Bureau of Indian Standards.