

Electric Vehicle Charging Station Challenges and Opportunities: A Review

Vishal Jatav¹, Ashish Bhargava²

¹Student, ²Professor,

^{1,2}Bhabha Engineering Research Institute, Bhopal, Madhya Pradesh, India

ABSTRACT

Electric Vehicles (EV) are the ideal replacement to Internal Combustion Engine (ICE) vehicles after the environmental crisis. However, concentrating just on EVs is insufficient since Electrical Vehicle Charging Stations (EVCS) are also required for the deployment of these cars. Because these cars are fuelled by electricity, deploying these charging stations presents several difficulties. Grid overload and load forecasting were once big issues. The latter refers to charging time and charging station traffic-crowd management. This document discusses fundamental charging station terms such as charging station kinds and levels. Various technologies are presented in order to solve these issues, as well as a short introduction to lithium-ion battery charging schemes and the Battery Management System (BMS). Since the Indian government is focusing on creating a more environmentally friendly ecosystem, and as part of its objective to reduce carbon emissions from the transportation sector, the deployment of EVs and the construction of EVCS is of the utmost importance. This is a simple chore now that the government has decreased the tax on EVs and provided subsidies for the installation of charging stations. As a result, various rules issued by the Ministry of Power and the Ministry of Housing (Government of India) are presented in this document, which might assist a person in setting up a charging station at their location.

KEYWORD: *Electrical Vehicle (EV); Electrical Vehicle Charging Station (EVCS); Renewable Energy Sources (RES); Smart Grid; Battery Swapping Station (BSS); Intelligent Trans- port System (ITS); Vehicle to Grid (V2G)*

I. INTRODUCTION

With the increase in carbon emission, global warming and oil crisis in all over the world a revolutionary change can be identified in the field of automobiles in terms of shifting of ICE based vehicles to EVs. Since oil is the primary fuel used in ICE vehicles which is the major reason of global environmental crisis, EVs are the best alternative [1]. Apart from being eco-friendly these vehicles can provide other advantages like less moving parts, high starting torque, high power density, good efficiency, etc. by replacing internal combustion engine from electrical motors like DC series motor, brushless DC (BLDC) motor, permanent magnet synchronous motor, induction motors, switched reluctance motor (SRM) [2]. The main power source to these motors is electrical batteries. The major challenge for these electrical

How to cite this paper: Vishal Jatav | Ashish Bhargava "Electric Vehicle Charging Station Challenges and Opportunities: A Review" Published in International

Journal of Trend in Scientific Research and Development (ijtsrd), ISSN: 2456-6470, Volume-6 | Issue-2, February 2022, pp.1232-1240,

www.ijtsrd.com/papers/ijtsrd49422.pdf



URL:

Copyright © 2022 by author (s) and International Journal of Trend in Scientific Research and Development Journal. This is an Open Access article distributed under the terms of the Creative Commons Attribution License (CC BY 4.0) (<http://creativecommons.org/licenses/by/4.0>)



vehicles is charging of these batteries in minimum time and for which electrical vehicle charging station plays a vital role. Charging station can be of various types depending upon the level of charging [1]. There are various standards codes like Society for Automobile Engineers (SAE), International Energy Agency (IEA), Institute of Electrical and Electronic Engineering (IEEE), International Electromechanical Commission (IEC) and International Organization for Standardization which provides the guidelines and voltage level to charge the vehicle according to its rated capacity [1].

There are various challenges to deploy Electric Vehicle Charging Station (EVSE). Day by day the numbers of vehicles are increasing on road and that

requires more electrical power. This will pressurize the grid to supply more electrical power which can overload the grid and the generation of power will have to increase which if generated using fossil fuels will equally harm the environment as that of ICE vehicles [3]. Apart from that, overloading of grid can cause voltage regulation issue, voltage fluctuation, increase in peak demand, reliability and efficiency of the system will decrease, thermal loading will increase and most important affect can be seen on load forecasting. Load Forecasting is very crucial in the electrical distribution system for determining how much power is to be generated by calculating the peak load and base load [1], [3]. But after the deployment of EVs and EVCS, the load forecasting of the system is becoming difficult as calculation of the varying load is biggest challenge.

Byungchul Kim, [4] develop a smart charging architecture between electric vehicle and smart home in which the system is comprises of sensors and processors which can help a lot in vehicle to grid(V2G) technology by setting a communication channel in between. By the help of this technology proper monitoring of the load due to charging of vehicle can be monitored. With the help of V2G technology and Intelligent Transport System (ITS) the waiting time at the charging station can also be reduced and Dimitrakopoulos. G [5] discussed about the internet of vehicle concept and automatic management algorithm for vehicles in which with the help of Information and Communication Technology (ICT) vehicles, grid and charging station can communicate with each other on the basis of IP-based level. This can help in reduction of traffic congestion and long queue problems at EVCS. Charging time of the vehicle is also one of the biggest challenges in the development of the EVs. Lithium ion batteries are used as a storage medium of electrical energy in these vehicles and these batteries use graphite for storing charge. To increase the charge storing capacity of lithium ion batteries silicon is added in graphite layer. Proper charging of the batteries is very necessary for its long life. Since charging a lithium ion battery is a very sensitive process as overvoltage and overheating can cause a severe problem hence there are various charging strategies like Constant Current, Constant Power, Constant Voltage, Constant Current Constant Voltage and multistage charging [6]. Kodali S and et al. [7] discusses the five level charging scheme of the lithium ion batteries in which five different levels of current as per the voltage limit is used to charge the battery. But while charging these batteries proper monitoring of the State of Charge (SOC) of battery is required which shows how much battery is charged or

discharged. For monitoring purpose and smooth operation of process Battery Management System (BMS) is used. BMS not only monitors the charge density and SOC level but it also provide the information of the temperature and failure of each lithium ion cell present in the battery [8], [9], [10]. BMS and SOC level can help in forecasting the load using the Internet of Things (IOT) which can help in overcome the problems of power quality and reliability.

II. ELECTRIC VEHICLE CHARGING STATION

EVCS is a place where the charging of EV takes place with proper safety, monitoring, conversion system and with high voltage and current for the fast charging. Some of the basic terminologies related to EVCS are.

A. Types of Charging Station

1. Residential Charging Station: To enter in the era of EV, residential charging station is very important as it will reduce the load on the grid at a great extent. The residential charging of vehicles can be done by drawing less current from the grid which will help the grid to overcome the demand of extra voltage at peak load hours. According to [11] charging of EVs at night hours is the best time to charge a vehicle and is very effective in terms of cost and impact on grid. It reduces the load on grid as it is the base load hours and charging vehicles in night time also reduces per unit cost of electricity. Vehicles can easily charge within 7 to 8 hours by Level 1 charging in residential charging station as shown in Table. I.

2. Parking Charging Station: Charging a vehicle is a time taking process but by utilizing the time while parking a vehicle will reduce the stress on the public charging station as well as on grid. According to National Household Travel Survey, vehicles are parked around five hours in a day at work place [12]. Apart from work place this facility is also taking place at restaurants, shopping malls, library etc. with proper charging infrastructure policies. Existing parking lot are converted into smart charging parking lot having connectivity with the internet for slot booking and traffic enquiry at parking area [13]. Mainly in such place Level 2 charging is used having both single phase and three phase slot [14].

3. Public Charging Station: The provision of public charging station is introduced to provide fast charging to the vehicles as normal charging takes more time to charge a battery. With the help of various charging topologies and fast charger

configuration fast charging is carried out. Mainly in a charging station the charger consists of AC-DC converter at front end and DC-DC Converter at back end. Both the converter is connected via DC link capacitor [15].

Chargers having high frequency switching rectifiers are made up of MOSFET and IGBT that works on the principle of Pulse Width Modulation (PWM) scheme. PWM scheme provides power conversion with high efficiency and precision and it also control the output voltage by maintaining the power factor near to unity [16]. Due to the presence of power electronics devices charging a vehicle can cause power quality issues like harmonics, voltage imbalance etc. For this the connection of charger by power grid is done by using a filter of good quality which will resist the harmonics to effect the grid as well as motor connected to vehicle [15], [17].

4. Battery Swapping Station: To overcome the problem of time taken in charging and the urgent requirement of charged vehicle Battery Swapping Station (BSS) was introduced. In a BSS vehicle's discharged battery or battery pack can be immediately swapped by a fully charged one, eliminating the delay involved in waiting for the vehicle's battery to charge. The BSS takes care of the battery life by monitoring it using BMS. It determines the energy density of battery along with the SOC level [18]. There are various challenges while deploying a BSS. Battery design is one of the major issues which can be resolved by designing battery pack in a specific way so that it can easily and rapidly removed from vehicles and so rapidly re-attached. Another challenge is brand compatibility of the battery packs. For this a common standard format can be used by the manufactures so that the interchangeable battery packs can be manufactured for BSS and EVs. There are also battery degradation issue and battery ownership issue which is the main obstacle in the BSS technology.

B. Levels of Charging

As per various international standards and codes for charging vehicles the level of charging are given in Table I [1].

C. EV Charging System

The EV charging systems can be classified according to the mode of energy transfer such as: conductive charging systems and inductive charging systems.

1. Conductive Charging: This charging system uses direct contact between the vehicle and

charger using a cable or connector. This is the basic infrastructure of the charging station now. It can be On-Board charging or off board charging depending upon the level of charging. This type of charging provides better efficiency and almost all the electric vehicle company provides the facility of such charging. Conductive charging systems are currently available in vehicles such as: Nissan Leaf, Chevrolet Volt, Mitsubishi i-MiEV and Tesla Roadster [1], [6].

2. Inductive Charging: A new emerging concept named as inductive charging or wireless charging in which no physical contact or linkage is provided between the vehicle and charger is in growing phase. It works on the principle of the electro-magnetic induction same as the principle of the transformers. [6], [22]. The wireless transmission charging is carried out by determining the distance between the primary and secondary coil. Magnetic field is used to transfer energy through thin air. The only drawback is that its efficiency and power density is very low as compare to the conductive charging and cost is high [1]. But it is convenient in terms that charging can be carried out without hassles of plugging and unplugging of the heavy charging plugs. Vehicles can be charged irrespective of the size and compatibility of the connector.

By incorporating charging strips at the highway the vehicles can be charged while driving also. This is called as dynamic wireless charging. Roads that are capable of supplying electric power to electric vehicle using wireless power technique (WPT) are called electrified roads or charging lane [1], [23]. Charging while driving technique will reduce the charging time of vehicles at stationary position [1]. This method is ongoing at various countries and more researches are going on to increase its efficiency [24].

D. Charging Time

Charging time is one of the biggest challenge in the EV technology. Recharging time of the battery is higher than refueling time of oil in ICE vehicles. To reduce the charging time there are mainly 5 factors discussed below that affect the fast charging of system [25].

- Size of the battery: The charging time will increase as the capacity or size measured in kWh will increase. Bigger
- the battery more time it will take to charge the battery.
- State of charge (SOC): SOC of the battery helps to determine whether battery is fully charged, fully discharged or partial discharged and according to that the charging time varies.

- Maximum charging rate of vehicle: The vehicle can be charged at a maximum rate of charge only and not beyond that. Suppose if the maximum rate of charge of any battery is 22kW then it cannot be charged using a 50kW charge point.
- Maximum charging rate of the charge point: The time of charging depends on the rating of outlet where the battery is connected. To charge a battery of 22kW if a 7kW outlet is connected it

will charge it in same rate as of 7kW that means the charging time increase [25].

Normally the charging time is 8 hours if the battery is charged from a 7kW charger and it can be used till 60 miles. Table II summarizes the time required to charge a battery of different company vehicle with different rate of chargers. Where, Model I: Nisan Leaf 2018, Model II: Tesla Model S 2019, Model III: Mitsubishi Outlander PHEV 2018 respectively.

TABLE I. CHARGING LEVELS [19], [20], [21]

Level of Charging	Phase	Type of Charger	Usage and Location	Power (kW) and current(A)
As per SAE standard for AC and DC charging				
Level 1: Vac= 230V (EU) Vac=120V(US)	Single Phase	On Board	Residential and Office	1.4kW/12A, 1.9kW/20A
Level 2: Vac= 400V (EU) Vac= 240V (US)	Single/Three phase	On Board	Public and Private	4kW/17A, 8kW/32A
Level 3- Fast: Vac:=208-600 V	Three Phase	Off Board	Commercial and Filling Station	50kW, 100kW
DC Power Level 1: Vdc= 200-450V		Off Board	Dedicated Charging Stations	40kW/80A
DC Power Level 2: Vdc= 200-400V		Off Board	Dedicated Charging Stations	90kW /200A
DC Power Level 3: Vdc= 200-600V		Off Board	Dedicated Charging Stations	240kW /400A
As per IEC standards for AC and DC Charging				
AC Power Level 1	Single Phase	On Board	Residential and Office	4-7.5kW/16A
AC Power Level 2	Single/Three phase	On Board	Public and Private	8-15kW/32A
AC Power Level 3	Three Phase	On Board	Commercial and Filling Station	60-120kW/250A
DC Rapid Charging		Off Board	Dedicated Charging Stations	1000-2000kW/400A
CHAdEMO Charging Standard				
DC Rapid Charging		Off Board	Dedicated Charging Stations	62.5kW/125A

TABLE II. CHARGING TIME OF VEHICLE [25].

Model	Battery Capacity (kWh)	Range (miles)	Charging Time(hours)				
			3.7 kW	7 kW	22 kW	43-50 kW	150 kW
I	40	143	11	6	6	1	NA
II	75	238	21	11	5	2	1
III	13.8	24	4	4	4	0.66	NA

III. RECENT TECHNOLOGIES FOR EFFICIENT SYSTEM

Deployment of large number of charging station increases the need of electrical power. So more the power will be drawn from the grid, grid will become overloaded and due to which various power quality issues rises like voltage fluctuation, voltage regulation issue, peak demand issue, reliability and load forecasting. All these issues affect the overall efficiency of the system which is not admissible for development of EV and EVCS. So to overcome these challenges there are various technologies introduce as:

A. Smart Grid Technology

The problem of uncoordinated power supply and reliability can be minimized to a certain extent by using the smart grid technology. The smart grid set up a communication channel between the grid and the user for proper

monitoring of load as per the area [26]. By the implementation of smart grid safe operation of system can be assured as at each feeder the remote terminal units are installed which send the information of any fault condition as well as the usage of power at each feeder. This technique can give prior information to grid about the load so that at generation end smooth generation can be assured and thus no reliability issue takes place [26], [27]. Moreover this technique is also helpful in forecasting load and linked with the vehicle so that the SOC of a battery can be shared with the grid and according to the SOC percentage the grid can trace the nearby charging station to which feeder the load is going to add [27]. Now, when distributed energy generation is at its peak, smart grid works as an extraordinary technique to provide proper load and generation estimation.

B. Renewable Energy Technology

Fossil fuels are the major reason of degradation of environment and these are the major source of electricity generation today. Adoption of more EVs requires more electrical power. So it is not a wise decision to again use these fossil fuels in different manner to fulfill the needs. Renewable sources of energy are the best alternative for charging EVs as these sources will reduce the carbon emission as well as the load on the grid [28], [29]. Among all renewable sources of energy solar energy is the easiest and cheapest form available at various part of the world today. Installing the solar plant at residence level is also easy and safest mode of obtaining electrical power. Solar panels can be installed on the roof of the public EVCS, shopping malls, office and other places having large surface area so that direct load on the grid can be reduced [28]. Although installing solar plant on roof top is bit costly initially but its running cost is very cheap so it also decreases the running cost of EVs as compare to ICE based vehicles.

C. Vehicle to Grid Technology

To keep the power system balance there should be a balance between the active power and frequency as the overloading and under loading can create an issue of frequency mismatch which can affect the systems stability. So it is recommended to use bidirectional energy flow system where the grid supply power to vehicle and when not in use the vehicle feed the power to the grid. This system is also called vehicle to grid system or V2G system [30]. Statistics says that 90 % of electrical vehicles are idle every day and they can be helpful to meet the high energy demand by supply power back to grid [31]. Automatic generation control (AGC) was introduced to control the modern power network to keep a balance of varying load. Traditional AGC regularize generating unit to respond to load fluctuation. With the help of residential small solar plant which is not charging the vehicle at that moment it can be helpful to decrease the load on grid as this generating power can be fed back to the grid. This will be the pure or green form of electrical power and cost effective also [11], [31].

D. Intelligent Transport System

To make the system smarter Intelligent Transport System (ITS) came into picture. This system comprises of sensors, actuators and embedded processor which helps to track the traffic congestion of the particular area. In other words, it set up a communication channel between two or more with the charging station or parking lot. By the medium of internet or mobile network and on-board Geographical Information Systems (GIS), Global Positioning Systems (GPS) and advanced traffic flow modeling techniques this communication can be easily done [5], [32]. The monitoring and control of the process can be done through Internet of Things (IOT). IOT is also helpful in determining the SOC of the EV battery and send this information to the grid so that the proper monitoring of load can be carried out. Apart from that the pre booking of slot at charging station and knowing the status of empty slot can be easily done using this technology [11], [5], [32]. This technique made the load forecasting effective and can easily communicate with the renewable sources based generating plant either at home, office, parking lot, shopping mall or charging station [5], [32].

IV. CHARGING TECHNIQUES OF BATTERY Lithium ion batteries are now days best known batteries

in terms of energy density and longevity for EVs. These batteries comprise of various cells connected in series and then in parallel to form a module and various modules are connected in series to form a battery pack. Usage of various cells helps in good maintenance and monitoring of battery [33]. The biggest challenge today is to charge these batteries efficiently and faster. Some of the charging techniques are:

A. Constant Current Charging Scheme

In this scheme battery is charged using constant current or uniformly constant current. If more number of cells is associated then this method is not used because this can lead to the issue of cell balancing. Hence, this method is inefficient and can put cells in stress [7]. To implement this method on the lithium ion batteries high current is required which undoubtedly charge the battery faster but in the mean time the temperature of the battery will rise

which can lead to the sudden death of the battery. Another reason is that high current will increase the rate of travelling of lithium ion in the graphite layer but if the rate is faster than the ions will not insert in graphite layer properly and can deposit on the electrodes leads to lithium plating. So extra time is required by lithium ions to get deposit in the layer hence indirectly it increases the time of charging [7], [8].

B. Constant Current Constant Voltage Charging Scheme

In this scheme basically there are 4 modes to charge a battery [7].

- Pre Charge Mode: In this mode 10 % of battery is charged using full current to avoid overheating of cell.
- Constant Current Mode: The battery is below 1C rate until battery reaches 4.2 V. this will increase the voltage.
- Constant Voltage Mode: The battery is charged at constant voltage of 4.2V until it reaches 100 % SOC. Although battery shows full charge but still there is space required to charge, because of overheating issue of constant current method the battery is then charged with constant voltage.
- Charge Termination Mode: Termination of charge is carried out using minimum charge current method by monitoring charge current as it reaches 0.02-0.07C the charge is terminated.

Having all these advantages, this method is still not in use so much as it takes lots of time to charge a battery completely.

C. Multistage Charging Scheme

All above mentioned method has drawback of more charging time. But in this method the battery is charged at various current levels and each level has its own voltage limit. Since high current can increase the temperature of the battery this method was introduced [7]. For fast charging of the battery high current is required to charge the battery when internal resistance of the battery is low and decrease the charging current when the internal temperature is high. According to the charging rate and SOC these charging current value and threshold voltage limits are decided. This method can charge battery faster, efficiently without harming battery life [9].

V. INDIAN CONTEXT

Indian Government is focusing more on reducing the carbon emission rate and for which it is taking all the necessary steps. India is in one of the top 10 countries having vast automobile market [34]. Hence using more and more oil based vehicle degrades the environment. According to National Electric Mobility Mission Plan (NEMMP) 2020 [35], around 5 to 7 million electric vehicles should be run on road by 2020 which will reduce the carbon emission by vehicle by 1.3%. As per the Indian Government vision of generation of electric power using renewable sources of energy, around 175GW power can be only generated using the clean energy source by 2022 out of which 100GW will be generated only by the solar [36], [37]. This step of government will be so helpful to install more and more charging station and residential charging station without putting any extra load on the grid. Ministry of Power and Ministry of housing and urban affairs provides some of the basic guidelines and standards to install a public charging station [38], [39] as follows.

1. It is a de-licensed activity that is any person is free to install a charging station. But the person needs to inform the electricity distributor to take proper electricity connection.
2. Any charging station can obtain electricity from any generation company either private or public or by generating their own power using solar panels or wind mills or etc.
3. At charging station a exclusive transformer is required having all the safety devices connected at their sub-station or switchgear room.
4. Adequate space in the station for movement of the vehicles.
5. Proper civil work and fire fighting work should be done
6. For deploying public charging station at least 5 chargers of rating given in Table III is necessary. It is not necessary to use only these companies charger given in the table III. Owner can use any connector but it should meet the standards and specification as that of these chargers and provided by BIS standards. According to the number of EVs the number of charging points can be increased but the minimum criteria of at least 5 chargers should be fulfilled.
7. As far as the distance is concerned it is recommended to set up a charging station within 3 km range in city and on highways at each 25km there should be a charging station. This distance can be minimized as per the choice of installing more stations but it should not be more.

According to the Ministry of Housing (Government of India) in electrical vehicle charging infrastructure, EVSE is very important. EVSE are classified or installed as per the levels of charging of EVs, charging speed and requirement. It is different for private, public and commercial CS [39].

TABLE III. TYPES OF CHARGERS REQUIRED [38]

Charger Type	Charger Connector	Minimum Power (kW)	Rated Voltage(V)	No. of Charging Point
Fast	CCS	50	200-1000	1
	CHAdeMO	50	200-1000	1
	Type 2 AC	20	380-480	1
Slow/ Moderate	Bharat DC 001	15	72-200	1
	Bharat AC 001	10	230	3

VI. CONCLUSION

The obstacles of implementing a charging station are examined in this study in terms of grid overloading, battery charging time, and traffic congestion caused by increased waiting time at EVCS. Various technologies are being explored in order to tackle these issues. The planned employment of these technologies may improve the overall reliability and efficiency of the electrical transportation system. This page also discusses several charging procedures, since the battery is the key component of an electric vehicle that must be charged effectively without causing internal damage. Multistage charging is the most popular method of rapid charging without causing battery deterioration. Because India is a growing nation pursuing environmentally friendly growth, the deployment of EVs and EVCS is critical. One of the major factors influencing a country's growth is its transportation infrastructure. So, in order to deploy EVCS in India, various principles and standards are being debated, which may assist to bring about a revolutionary transformation in the vehicle industry. The adoption of all-electric vehicles may result in a significant improvement in the environment. This will make a significant contribution to a more sustainable future. However, before implementing them, authorities must create additional charging stations capable of charging batteries quicker and using renewable energy sources. There is now a lot of research being conducted to make the whole system more trustworthy.

REFERENCES

- [1] S. Habib, M. M. Khan, F. Abbas, L. Sang, M. U. Shahid, and H. Tang, "A comprehensive study of implemented international standards, technical challenges, impacts and prospects for electric vehicles," *IEEE Access*, vol. 6, pp. 13 866–13 890, 2018.
- [2] J. G. West, "Dc, induction, reluctance and pm motors for electric vehicles," *Power Engineering Journal*, vol. 8, no. 2, pp. 77–88, 1994.
- [3] Z. Zhang and D. Gu, "Impacts of charging plug-in hybrid electric vehicles on the electric grid and its charging strategies," in *2012 Power Engineering and Automation Conference*. IEEE, 2012, pp. 1–4.
- [4] B. Kim, "Smart charging architecture for between a plug-in electrical vehicle (pev) and a smart home," in *2013 International Conference on Connected Vehicles and Expo (ICCVE)*. IEEE, 2013, pp. 306–307.
- [5] G. Dimitrakopoulos, "Intelligent transportation systems based on internet-connected vehicles: Fundamental research areas and challenges," in *2011 11th International Conference on ITS Telecommunications*. IEEE, 2011, pp. 145–151.
- [6] Zhang, X. Zhang, M. Zhang, and A. S. Edmonds, "Literature review of electric vehicle technology and its applications," in *2016 5th International Conference on Computer Science and Network Technology (ICCSNT)*. IEEE, 2016, pp. 832–837.
- [7] S. P. Kodali and S. Das, "Implementation of five level charging scheme in lithium ion batteries for enabling fast charging in plug-in hybrid electric vehicles," in *2017 National Power Electronics Conference (NPEC)*. IEEE, 2017, pp. 147–152.
- [8] Y. Yin, Y. Hu, S. -Y. Choe, H. Cho, and W. T. Joe, "New fast charging method of lithium-ion batteries based on a reduced order electrochemical model considering side reaction," *Journal of Power Sources*, vol. 423, pp. 367–379, 2019.
- [9] D. -R. Kim, J. -W. Kang, T. -H. Eom, J. -M. Kim, J. Lee, and C. -Y. Won, "An adaptive rapid charging method for lithium-ion batteries

- with compensating cell degradation behavior,” *Applied Sciences*, vol. 8, no. 8, p. 1251, 2018.
- [10] C. -W. Lan, S. -S. Lin, S. -Y. Syue, H. -Y. Hsu, T. -C. Huang, and K. -H. Tan, “Development of an intelligent lithium-ion battery-charging management system for electric vehicle,” in *2017 International Conference on Applied System Innovation (ICASI)*. IEEE, 2017, pp. 1744–1746.
- [11] S. Divyapriya, R. Vijayakumar *et al.*, “Design of residential plug-in electric vehicle charging station with time of use tariff and iot technology,” in *2018 International Conference on Soft-computing and Network Security (ICSNS)*. IEEE, 2018, pp. 1–5.
- [12] Santos, N. McGuckin, H. Y. Nakamoto, D. Gray, and S. Liss, “Summary of travel trends: 2009 national household travel survey,” Tech. Rep., 2011.
- [13] J. Babic, A. Carvalho, W. Ketter, and V. Podobnik, “Evaluating policies for parking lots handling electric vehicles,” *IEEE access*, vol. 6, pp. 944–961, 2017.
- [14] S. Habib, M. M. Khan, F. Abbas, L. Sang, M. U. Shahid, and H. Tang, “A comprehensive study of implemented international standards, technical challenges, impacts and prospects for electric vehicles,” *IEEE Access*, vol. 6, pp. 13 866–13 890, 2018.
- [15] S. Varghese, P. Thomas, and S. Varghese, “An efficient voltage control strategy for fast charging of plug-in electric vehicle,” in *2017 Innovations in Power and Advanced Computing Technologies (i-PACT)*. IEEE, 2017, pp. 1–4.
- [16] Deng and Z. Wang, “Research on electric-vehicle charging station technologies based on smart grid,” in *2011 Asia-Pacific Power and Energy Engineering Conference*. IEEE, 2011, pp. 1–4.
- [17] M. Di Paolo, “Analysis of harmonic impact of electric vehicle charging on the electric power grid, based on smart grid regional demonstration project los angeles,” in *2017 IEEE Green Energy and Smart Systems Conference (IGESSC)*. IEEE, 2017, pp. 1–5.
- [18] Zheng, F. Wen, and J. Huang, “Optimal planning of battery swap stations,” 2012.
- [19] “Characteristics of ChaDemo Quick Charging System,” <https://www.mdpi.com/2032-6653/4/4/818/pdf/>, 2019, [Online; accessed 27-July- 2019].
- [20] “SAE International standards work, including communication protocols and connectors, fast charge, batteries,” <https://share.ansi.org/Shared%20Documents/Meetings%20and%20Events/EDV%20Workshop/Presentations/Pokrzywa-ANSI-EDV-0411.pdf/>, 2019, [Online; accessed 27-July-2019].
- [21] “IEC 62196 Electric Vehicle Charge Connector Assembly (Type 2 for Mode 2 and 3),” <https://www.dalroad.com/wpcontent/uploads/2016/08/Type-II-connector-product-spec.pdf/>, 2019, [Online; accessed 27-July- 2019].
- [22] M. Yilmaz and P. Krein, “Review of charging power levels and in- frastructure for plug-in electric and hybrid vehicles and commentary on unidirectional charging,” in *IEEE International Electrical Vehicle Conference*, 2012.
- [23] Y. J. Jang, “Survey of the operation and system study on wireless charging electric vehicle systems,” *Transportation Research Part C: Emerging Technologies*, vol. 95, pp. 844–866, 2018.
- [24] N. Shinohara, “Wireless power transmission progress for electric vehicle in japan,” in *2013 IEEE Radio and Wireless Symposium*. IEEE, 2013, pp. 109–111.
- [25] “Charging Time of Battery,” <https://podpoint.com/guides/driver/how-long-to-charge-an-electric-car/>, 2019, [Online; accessed 27-July- 2019].
- [26] B. Deng and Z. Wang, “Research on electric-vehicle charging station technologies based on smart grid,” in *2011 Asia-Pacific Power and Energy Engineering Conference*. IEEE, 2011, pp. 1–4.
- [27] M. Yilmaz and P. T. Krein, “Review of battery charger topologies, charging power levels, and infrastructure for plug-in electric and hybrid vehicles,” *IEEE transactions on Power Electronics*, vol. 28, no. 5, pp. 2151–2169, 2012.
- [28] Y. -M. Wi, J. -U. Lee, and S. -K. Joo, “Electric vehicle charging method for smart homes/buildings with a photovoltaic system,” *IEEE Transactions on Consumer Electronics*, vol. 59, no. 2, pp. 323–328, 2013.
- [29] Mauri and A. Valsecchi, “The role of fast charging stations for electric vehicles in the integration and optimization of distribution grid with renewable energy sources,” 2012.

- [30] W. Tian, J. He, L. Niu, W. Zhang, X. Wang, and Z. Bo, "Simulation of vehicle-to-grid (v2g) on power system frequency control," in *IEEE PES Innovative Smart Grid Technologies*. IEEE, 2012, pp. 1–3.
- [31] S. Kori, "Vehicle-to-grid power implementation: From stabilizing the grid to supporting large-scale renewable energy," *Journal Current Science*, vol. 18, no. 12, 2017.
- [32] Q. Gong, Y. Li, and Z. -R. Peng, "Optimal power management of plug-in hev with intelligent transportation system," in *2007 IEEE/ASME international conference on advanced intelligent mechatronics*. IEEE, 2007, pp. 1–6.
- [33] Y. -s. Bai and C. -n. Zhang, "Experiments study on fast charge technology for lithium-ion electric vehicle batteries," in *2014 IEEE Conference and Expo Transportation Electrification Asia-Pacific (ITEC Asia-Pacific)*. IEEE, 2014, pp. 1–6.
- [34] Aswani, V. S. Bhadoria, and J. Singh, "Electric vehicles in india: Opportunities and challenges," in *2018 International Conference on Automation and Computational Engineering (ICACE)*. IEEE, 2018, pp. 65–71.
- [35] "National Electric Mobility Mission Plan (NEMMP) 2020," <https://dhi.nic.in/writereaddata/Content/NEMMP2020.pdf/>, 2019, [Online; accessed 29-July-2019].
- [36] "India's Journey towards 175 GW Renewables by 2022," <http://www.indiaenvironmentportal.org.in/files/file/Indias%20Journey%20towards%20renewable%20energy.pdf/>, 2019, [Online; accessed 28-July-2019].
- [37] "Guidelines for Implementation of Scheme for Farmers for Installation of Solar Pumps and Grid Connected Solar Power Plants," <https://mnre.gov.in/sites/default/files/webform/notices/NoticeInvitingCommentsonGuidelines.pdf/>, 2019, [Online; accessed 28-July-2019].
- [38] "Charging infrastructure of electrical vehicles Guidelines and Standards," <https://powermin.nic.in/sites/default/files/webform/notices/scan0016%20%281%29.pdf/>, 2019, [Online; accessed 28-July-2019].
- [39] "Electrical vehicle charging station Guidelines by ministry of housing," [http://mohua.gov.in/upload/whatsnew/5c6e472b20d0aGuidelines%20\(EVCI\).pdf/](http://mohua.gov.in/upload/whatsnew/5c6e472b20d0aGuidelines%20(EVCI).pdf/), 2019, [Online; accessed 28-July-2019].